

S915SE SOFT EDGE ROLL-FAST DOOR

INTERNAL DOOR WITH SOFT EDGE BOTTOM PROFILE



*S915SE with a
flexible curtain –
robust, fast and
efficient*



S915SE SOFT EDGE ROLL-FAST DOOR

INTERNAL DOOR WITH SOFT EDGE BOTTOM PROFILE



The Internal door with a Soft Edge bottom profile

The S915SE Roll-Fast Door is particularly efficient thanks to the anti-crash system.

When goods are being transferred between areas, it is important that a crash does not hold up the process - an internal door must be operative again as quickly as possible. Thanks to the SoftEdge bottom profile with anti-crash system, M.T.I. offers the optimum solution: efficient and at the same time safe.

Control Options

- Inductive Loops
- Microwave Sensors
- Push Buttons
- Infrared Sensors
- Remote Control
- Interlock Facility



Panel Colours

- Yellow
- Blue
- Black
- Red



S 915SE Door specifications

APPLICATION: Internal.

DOOR SIZE: Height max: 5000mm
Width Max: 5000mm

DOOR SPEED:

Opening: 0.8/1.5 m/s Closing: 0.8/0.8 m/s

CURTAIN THICKNESS:

Fabric/vision panel 1.5/2.0 mm

WIND PROTECTION:

Aluminium profile.

ANTI-CRASH SYSTEM:

Soft Edge System

INVERSION RELAY CONTROLS:

Frequency converter controls on request.

OPTIONS:

Emergency opening via counterweight

Operator/shaft cladding

Stainless steel version